


MANUFACTURER NOTES

- IF SELF TAPPING SCREWS PENETRATE WEATHER BARRIER, THESE LOCATIONS MUST BE SEALED.
- TEK SCREWS MAY BE USED AT ALL 4" CLIP LOCATIONS WHEN MOUNTED OVER CONTINUOUS INSULATION SYSTEM.
- REVEAL GAP MUST BE 1/2" MINIMUM TO REPLACE PANELS NON-SEQUENTIALLY.
- .125" VITRAPLATE MAY ALSO BE USED.

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5444-051.



FLUSH PANEL SYSTEM

VITRABOND FR: FLUSH PANEL SYSTEM CONDITION A - TYPICAL VERTICAL DETAIL