



#### NOTES:

IF SELF TAPPING SCREWS  
PENETRATE WEATHER  
BARRIER, THESE LOCATIONS  
MUST BE SEALED

TEK SCREWS MAY BE USED AT  
ALL 2.5" CLIP LOCATIONS WHEN  
MOUNTED OVER CONTINUOUS  
INSULATION SYSTEM

REVEAL GAP MUST BE 1/2"  
MINIMUM TO REPLACE  
PANELS NON-SEQUENTIALLY

.125" VITRAPLATE  
MAY ALSO BE USED

|                |   |                              |   |  |
|----------------|---|------------------------------|---|--|
| Sheet<br><br>4 | Drawn By<br>NCDS  | Project Number<br><br>DWG-01 | Project<br><br>ARROWHEAD FLUSH SYSTEM<br>CONDITION A - TYPICAL VERTICAL DETAIL<br><br>© Copyright Fairview Architectural LLC - Patented and/or Patent Pending | <br><br><small>BY FAIRVIEW ARCHITECTURAL</small><br><small>ARCHITECTURAL PANEL SYSTEMS</small><br><small>www.fairview-na.com</small> |
|                | Date Drawn<br>1/9/2018                                    |                              |   |  |
|                | Revisions<br>No. _____ Date _____<br>No. _____ Date _____ |                              |   |  |