

IF SELF TAPPING SCREWS  
PENETRATE WEATHER  
BARRIER, THESE LOCATIONS  
MUST BE SEALED

#12 X 3/4" SELF DRILLING TEK  
SCREWS MAY BE USED WITH  
EXTERIOR INSULATED WALLS

SOLID BACKER  
BY OTHERS

#12 X 3/8" SELF  
TAPPING SCREW  
(2) PER CLIP

AH-204E  
AT CORNERS  
TO RUN FULL LENGTH  
BETWEEN  
HORIZONTAL BASES

SHIM AS REQ'D

AH-104  
T-CLIP

1/2"  
MIN.

#12 X 1/2" SELF  
TAPPING SCREW  
(1) PER CLIP

AH-204E AT CORNERS TO  
RUN FULL LENGTH BETWEEN  
HORIZONTAL BASES

5/32" ALUMINUM  
CSK RIVET  
@ MIN. 16" O.C.

2"  
NOMINAL

OUTLINE OF  
AH-202  
BASE BELOW

OUTLINE OF SHIM  
BELOW

WEATHER BARRIER  
AS REQUIRED.  
DESIGN BY  
ARCHITECT

4 MM VITRABOND  
FR CORE MCM

AH-104  
T-CLIP

AH-101  
FRAME  
EXTRUSION

1"  
2"  
MIN

Sheet

9

Drawn By  
NCDS

Date Drawn  
10/12/2017

Revisions

No. \_\_\_\_\_ Date \_\_\_\_\_  
No. \_\_\_\_\_ Date \_\_\_\_\_

Project Number

DWG-01

Project

ARROWHEAD FLEX OUTSIDE CORNER DETAIL  
GRID INSTALLATION

© Copyright Fairview Architectural LLC - Patented and/or Patent Pending

**FAIRVIEW**  
ARCHITECTURAL  
**arrowhead**  
ARCHITECTURAL PANEL SYSTEMS

www.fairview-na.com