

IF SELF TAPPING SCREWS
PENETRATE WEATHER
BARRIER, THESE LOCATIONS
MUST BE SEALED

#10 X 3/8" SELF TAPPING
SCREWS MAY BE USED WITH
EXTERIOR INSULATED WALLS

CONT. INSULATION
W/ VERT. SUBGIRTS, TYP.

#10 X 3/4" SELF
DRILLING SCREW
(2) PER CLIP

AH-204E AT CORNERS
TO RUN FULL LENGTH
BETWEEN HORIZONTAL BASES

AH-104
T-CLIP

1/2"
MIN.

#10 X 3/4" SELF
DRILLING SCREW
(2) PER CLIP

1-5/8"
SHIM AS REQ'D

OUTLINE OF
AH-202
BASE BELOW

WEATHER BARRIER
AS REQUIRED.
DESIGN BY
ARCHITECT

AH-104
T-CLIP

OUTLINE OF SHIM
BELOW

4 MM VITRABOND
FR CORE MCM

AH-401
FRAME
EXTRUSION

AH-204E AT CORNERS
TO RUN FULL LENGTH
BETWEEN HORIZONTAL BASES

1"
2"
MIN

Sheet

9

Drawn By
JSJ

Date Drawn
10/03/18

Revisions

No. Date

No. Date

Project Number

DWG-01

Project

ARROWHEAD LEAN OUTSIDE CORNER DETAIL GRID INSTALLATION

© Copyright Fairview Architectural LLC - Patented and/or Patent Pending

FAIRVIEW
ARCHITECTURAL
arrowhead
ARCHITECTURAL PANEL SYSTEMS

www.fairview-na.com