

IF SELF TAPPING SCREWS
PENETRATE WEATHER
BARRIER, THESE LOCATIONS
MUST BE SEALED

#10 X 3/8" SELF TAPPING
SCREWS MAY BE USED WITH
EXTERIOR INSULATED WALLS

CONT. INSULATION
W/ VERT. SUBGIRTS, TYP.

#10 X 3/4" SELF
DRILLING SCREW
(2) PER CLIP

WEATHER BARRIER
AS REQUIRED.
DESIGN BY
ARCHITECT

SHIM AS REQ'D

AH-207
STARTER CLIP

OUTLINE OF
AH-202
BASE BELOW

1-5/8"

AH-107
PERIMETER CLIP

AH-401 FRAME
EXTRUSION

4 MM VITRABOND
FR CORE MCM

3/4"
MIN.

BACKER ROD
& SEALANT
BY OTHERS

<p>Sheet</p> <p>10A</p>	<p>Drawn By JSJ</p> <p>Date Drawn 10/03/18</p> <p>Revisions</p> <p>No. _____ Date _____</p> <p>No. _____ Date _____</p>	<p>Project Number</p> <p>DWG-01</p>	<p>Project</p> <p>ARROWHEAD LEAN VERTICAL START DETAIL GRID INSTALLATION</p> <p>© Copyright Fairview Architectural LLC - Patented and/or Patent Pending</p>	<p>FAIRVIEW ARCHITECTURAL</p> <p>arrowhead ARCHITECTURAL PANEL SYSTEMS</p> <p>www.fairview-na.com</p>
-------------------------	---	-------------------------------------	---	---