

IF SELF TAPPING SCREWS
PENETRATE WEATHER
BARRIER, THESE LOCATIONS
MUST BE SEALED

#12 X 3/4" SELF DRILLING TEK
SCREWS MAY BE USED WITH
EXTERIOR INSULATED WALLS

SOLID BACKER
BY OTHERS

#12 X 3/8" SELF
TAPPING SCREW
(2) PER CLIP

AH-204E
AT CORNERS
TO RUN FULL LENGTH
BETWEEN
HORIZONTAL BASES

SHIM AS REQ'D

AH-104
T-CLIP

1/2"
MIN.

#12 X 1/2" SELF
TAPPING SCREW
(1) PER CLIP

AH-204E AT CORNERS TO
RUN FULL LENGTH BETWEEN
HORIZONTAL BASES

5/32" ALUMINUM
CSK RIVET
@ MIN. 16" O.C.

2"
NOMINAL

OUTLINE OF
AH-202
BASE BELOW

OUTLINE OF SHIM
BELOW

WEATHER BARRIER
AS REQUIRED.
DESIGN BY
ARCHITECT
3MM VITRAPLATE
SOLID ALUMINUM
PLATE MATERIAL

AH-104
T-CLIP

AH-101
FRAME
EXTRUSION

1"
2"
MIN

Sheet

9

Drawn By

NCDS

Date Drawn

10/12/2017

Revisions

No. _____ Date _____
No. _____ Date _____

Project Number

DWG-01

Project

ARROWHEAD FLEX OUTSIDE CORNER DETAIL
GRID INSTALLATION

© Copyright Fairview Architectural LLC - Patented and/or Patent Pending

FAIRVIEW
ARCHITECTURAL

arrowhead
ARCHITECTURAL PANEL SYSTEMS

www.fairview-na.com