

IF SELF TAPPING SCREWS  
PENETRATE WEATHER  
BARRIER, THESE LOCATIONS  
MUST BE SEALED

#10 X 3/8" SELF TAPPING  
SCREWS MAY BE USED WITH  
EXTERIOR INSULATED WALLS.

SUBSTRATE  
BY OTHERS

#12 ANCHOR  
(2) PER CLIP  
SEE NOTES  
7, 8 & 9  
SHEET 1

WEATHER BARRIER  
AS REQUIRED.  
DESIGN BY  
ARCHITECT

2" NOMINAL

AH-104  
T-CLIP

AH-204  
VERTICAL  
CLIP

MIN. EDGE DISTANCE  
SEE NOTES 7, 8 & 9  
SHEET 1

AH-204  
VERTICAL  
CLIP  
AH-104  
T-CLIP

$\frac{5}{32}$ " RIVET  
SEE NOTE 6  
SHEET 1

3MM VITRAPLATE  
SOLID ALUMINUM  
PLATE MATERIAL

$\frac{1}{2}$ " MIN

Sheet

8

Drawn By

JSJ

Date Drawn

10/12/23

Revisions

No 1 Date 1/18/21

No Date

Project Number

DWG-01

Project

ARROWHEAD FLEX OUTSIDE CORNER DETAIL  
CLIP INSTALLATION

© Copyright Fairview Architectural LLC - Patented and/or Patent Pending



www.fairview-na.com