

WINDOW SYSTEM
(BY OTHERS)

BACKER ROD &
SEALANT
(BY OTHERS)

FLASHING AND/OR
WATER RESISTIVE
BARRIER BY INSTALLER

AH-203 HEAD

AH-107
PERIMETER CLIP

AH -301
FLUSH FRAME

1" x .062" 3M VHB
TAPE G16F

OPTIONAL STRUC'L
CAULK FOR ADDED
STRENGTH

4MM VITRABOND
MCM

SHIM AS
REQ'D BY
OTHERS

NOTES:

IF SELF TAPPING SCREWS
PENETRATE WEATHER
BARRIER, THESE LOCATIONS
MUST BE SEALE

TEK SCREWS MAY BE USED AT
ALL 2.5" CLIP LOCATIONS WHEN
MOUNTED OVER CONTINUOUS
INSULATION SYSTEM

EVEAL GAP MUST BE 1/2"
MINIMUM TO REPLACE
PANELS NON-SEQUENTIALLY

0.125" VITRAPLATE
MAY ALSO BE USED

Sheet 11	Drawn By ED Date Drawn 10/15/2018 Revisions No _____ Date _____ No _____ Date _____	Project Number DWG-01	Project ARROWHEAD FLUSH SYSTEM TYPICAL SILL DETAIL © Copyright Fairview Architectural LLC - Patented and/or Patent Pending	 www.fairview-na.com
-----------------	---	------------------------------	---	--