

IF SELF TAPPING SCREWS
PENETRATE WEATHER
BARRIER, THESE LOCATIONS
MUST BE SEALED

#12 X 3/4" SELF DRILLING TEK
SCREWS MAY BE USED WITH
EXTERIOR INSULATED WALLS

5/8" TYPE X GYPSUM
WALLBOARD INTERIOR
(BY OTHERS)

WINDOW SYSTEM
(BY OTHERS)

MIN. 20GA STEEL
STUD, 24" O.C. MAX.

COUNTER
FLASHING
(BY OTHERS)

1/2" MIN. EXTERIOR
GYPSUM SHEATHING

AIR & VAPOR
BARRIER

#12 X 1/2" SELF
TAPPING SCREW
(1) PER CLIP
AH-206
END CLIP

3" POLYISO
INSULATION

OUTLINE OF
AH-202
BASE BELOW

AH-107
PERIMETER CLIP

4 MM VITRABOND
FR CORE MCM

3/4"
MIN

BACKER ROD
& SEALANT
BY OTHERS

AH-401 FRAME
EXTRUSION

Sheet 10B	Drawn By Date Drawn 02/15/2024 Revisions No _____ Date _____ No _____ Date _____	Project Number DWG-01	Project RAPIDWRAPCI NFPA285 COMPLIANT WALL ASSEMBLY TYPICAL LEAN VERTICAL JAMB DETAIL - END © Copyright Fairview Architectural LLC - Patented and/or Patent Pending	 www.fairview-na.com
-------------------------	---	-------------------------------------	--	--